

| | | | | | | | |
|---|---|---|--|----|----|--|--|
|  | GAMMA 112 SHOPLED® | 3500 lm / 2700 K 4000 lm / 3000 K | | 68 | 68 | | |
|  | GAMMA 115 SHOPLED® GAMMA 115 D SHOPLED® DIMMABLE GAMMA 115 TW SHOPLED® GAMMA 115 RGB SHOPLED® | Fortimo S 2000 lm / 3000 lm 3000 / 3500 / 4000 K Fortimo S 1100 lm / 2000 lm 3000 / 3500 / 4000 K LEXEL S TW 1100 lm 2700 - 4200 K LEXEL S RGB 800 lm | | 69 | 69 | | |
| | | | | 70 | 70 | | |
| | | | | 71 | 71 | | |
| | | | | 73 | 73 | | |





GAMMA 112

SHOPLED®

- spotlight for 3-circuit track
- 350° rotatable, ±80° pivotable
- 3-circuit multi adapter with preselectable phase adjustment and guide edge to avoid side-inverted installation
- incl. LED: 3500/4000 lm
- colour temperature: 2700/3000 K
- electronic driver embedded
- passive cooling
- housing: diecast aluminium, powder-coated
- reflector: pure aluminium (99,9%), silver-anodized
- basic colours: white, black, silver

LED
3500 lm
2700 K

LED
4000 lm
3000 K

| | | | | | | | | |
|-----------------|--|--|-------------------|-------------|--|--|--|---|
| characteristics | | | electr. specific. | | | | | |
| | | | | colour code | | | | article number + embedded colour code -_ _ - = order number |

| | with 3-circuit adapter | LED 3500 lm 2700 K | LED 4000 lm 3000 K | KG |
|------------|------------------------|--------------------------|--------------------------|-----|
| dimensions | | 8656.____.W | 8657.____.W | 2,4 |
| | | 8656.____.X | 8657.____.X | 2,4 |
| | | | | |
| | | | | |
| | | | | |

- Current wattage of LED module available on request
- 3-circuit monopoints for recessed or ceiling installation see page 95
- photometric data see page A20

GAMMA 115

SHOPLED®



- spotlight for 3-circuit track
- 350° rotatable, ±80° pivotable
- 3-circuit multi adapter with preselectable phase adjustment and guide edge to avoid side-inverted installation
- incl. Fortimo S LED: 2000/3000 lm
- colour temperature: 3000/3500/4000 K
- CRI_{Ra} > 85
- electronic driver embedded
- passive cooling
- housing: diecast aluminium, powder-coated
- reflector: pure aluminium (99,9%), silver-anodized
- basic colours: white, black, silver

LED Fortimo S
2000 lm
3000 K
3500 K
4000 K

LED Fortimo S
3000 lm
3000 K
3500 K
4000 K

| | | | | | | |
|---|--|--------------------|-------------|--|--|--|
| characteristics | | electr. spec. eff. | | | | |
| | | | colour code | | | |
| article number + embedded colour code -_._.- = order number | | | | | | |

| with 3-circuit adapter | | Fortimo S 2000 lm 3000 K | Fortimo S 2000 lm 3500 K | Fortimo S 2000 lm 4000 K | KG |
|------------------------|--|--------------------------------|--------------------------------|--------------------------------|-----|
| dimensions | | 8653._._.W | 8723._._.W | 8654._._.W | 2,3 |
| | | 8653._._.X | 8723._._.X | 8654._._.X | 2,3 |
| | | | | | |
| | | Fortimo S 3000 lm 3000 K | Fortimo S 3000 lm 3500 K | Fortimo S 3000 lm 4000 K | KG |
| | | 8718._._.W | 8719._._.W | 8720._._.W | 2,3 |
| | | 8718._._.X | 8719._._.X | 8720._._.X | 2,3 |

Current wattage of LED module available on request

3-circuit monopoints for recessed or ceiling installation see page 95

GAMMA 115 D SHOPLED®



- spotlight for 3-circuit track
- 350° rotatable, ±80° pivotable
- 3-circuit multi adapter with preselectable phase adjustment and guide edge to avoid side-inverted installation
- incl. Fortimo S LED: 1100/2000 lm
- colour temperature: 3000/3500/4000 K
- CRI_{Ra} > 80
- electronic driver embedded
- dimmable via trailing edge dimmer (100-20 %)
- „Touch & DALI“ version (100-10 %) on request
- passive cooling
- housing: diecast aluminium, powder-coated
- reflector: pure aluminium (99,9%), silver-anodized
- basic colours: white, black, silver

DIMMABLE

LED Fortimo S
1100 lm
3000 K
3500 K
4000 K

LED Fortimo S
2000 lm
3000 K
3500 K
4000 K

| | | | | | | | |
|-----------------|--|-------------------|-----------------------|---|---|-------|----|
| characteristics | | electr. specific. | 220-240 V 50-60 HZ | | ED | IP 20 | CE |
| | | | colour code | .01 .02 .28 | article number + embedded colour code -_._.- = order number | | |

| | | Fortimo S 1100 lm 3000 K | Fortimo S 1100 lm 3500 K | Fortimo S 1100 lm 4000 K | | KG |
|--|----|--------------------------------|--------------------------------|--------------------------------|--|-----|
| | MF | 8710._._.W | 8709._._.W | 8711._._.W | | 2,4 |
| | F | 8710._._.X | 8709._._.X | 8711._._.X | | 2,4 |
| | | | | | | |
| | | | | | | |
| | | Fortimo S 2000 lm 3000 K | Fortimo S 2000 lm 3500 K | Fortimo S 2000 lm 4000 K | | KG |
| | MF | 8712._._.W | 8717._._.W | 8713._._.W | | 2,4 |
| | F | 8712._._.X | 8717._._.X | 8713._._.X | | 2,4 |
| | | | | | | |

Current wattage of LED module available on request

3-circuit monopoints for recessed or ceiling installation see page 95

GAMMA 115 TW SHOPLED®



- spotlight for 3-circuit track
- 350° rotatable, ±80° pivotable
- 3-circuit multi adapter with preselectable phase adjustment and guide edge to avoid side-inverted installation
- incl. Lexel S TW LED: 1100 lm
- colour temperature: 2700-4200 K variable
- CRI_{Ra} > 80
- DALI/DMX 512 compatible
- dimmable 100-10 %
- electronic driver embedded
- passive cooling
- housing: diecast aluminium, powder-coated
- reflector: pure aluminium (99,9%), silver-anodized
- basic colours: white, black, silver

LED LEXEL S TW
 1100 lm
 2700 - 4200 K

| | | | | | | | |
|-----------------|--|-------------------|-------------|--|---|--|--|
| characteristics | | electr. specific. | | | | | |
| | | | colour code | | article number + embedded colour code -_._.- = order number | | |

| | | | | | | | |
|------------|------------------------|--|--|--|--|--|-----|
| dimensions | with 3-circuit adapter | Lexel S TW 1100 lm 2700 - 4200 K | | | | | KG |
| | | 8714._._.W | | | | | 2,4 |
| | | 8714._._.X | | | | | |

- Current wattage of LED module available on request
- 3-circuit monopoints for recessed or ceiling installation see page 95

GAMMA 115 RGB SHOPLED®



- spotlight for 3-circuit track
- 350° rotatable, ±80° pivotable
- 3-circuit multi adapter with preselectable phase adjustment and guide edge to avoid side-inverted installation
- incl. Lexel S RGB LED: 800 lm
- DMX 512 compatible
- electronic driver embedded
- passive cooling
- housing: diecast aluminium, powder-coated
- reflector: pure aluminium (99,9%), silver-anodized
- basic colours: white, black, silver

LED LEXEL S RGB
800 lm

| | | | |
|-----------------|--|-------------------|-----------------|
| characteristics | | electr. specific. | |
| | | | colour code |

article number + embedded colour code -...- = order number

| | with 3-circuit adapter | Lexel S RGB 800 lm | | | | KG |
|------------|------------------------|-----------------------|--|--|--|-----|
| dimensions | | 8715...W | | | | 2,4 |
| | | 8715...X | | | | 2,4 |
| | | | | | | |
| | | | | | | |

Current wattage of LED module available on request

3-circuit monopoints for recessed or ceiling installation see page 95